



<b>Model</b>	<b>LS-N3525U</b>
<b>System</b>	
Main Processor	ARM Cortex A9 Processor
Operating System	Embedded LINUX
<b>Video</b>	
Input	25 Channel, Support 4096×2160,2592×1944,2688×1520,2048×1536,1920×1080, 1280×960, 1280×720 ect. Incoming Bandwidth: 160MB
Output	1 VGA, 1 HDMI
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	25 Channel
Email Alarm	Support
<b>Display</b>	
VGA	Resolution: 800×600, 1024×768, 1280×720, 1280×1024, 1920×1080
HDMI	Resolution: 720P(1280×720), 1080P(1920×1080)
Display Split	25CHxD1/16CHxD1/9CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k
Digital Zoom	YES
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection
<b>Recording</b>	
Video Compression	H.264
Resolution	4k(4096×2160),5MP(2592×1944),4MP(2688×1520),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (704×576/704×480)
Record Rate	PAL : 4k@12×20fp,5MP@17×25fps,4MP@22×25fps,3MP@25×25fps,1080P@25×25fps, 960P@25×25fps,720P@25×25fps, D1@25×25fps NTSC: 4k@12×20fp,5MP@17×30fp,4MP@22×30fp,3MP@25×30fp,1080P@25×30fps, 960P@25×20fps 720P@25×30fps, D1@25×30fps
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	
Local Sync Playback	4chx1080P/1chx4MP/1chx5MP/1chx8MP(20fps)
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Network Functions	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows XP
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Hard Disk Driver</b>	
Interface Type	2 SATA Interface
Capacity	Up to 12TB capacity
<b>General</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/3A
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	354*245*45mm (L*W*H)
Weight	4.0KG (without HDD)